Appl. No. 09/802,289 Amdt. dated July 21, 2004 Reply to Office Action of April 27, 2004

## Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the application:

## Listing of Claims:

1. (Original) A processing core comprising:

one or more processing pipelines having a total of N-number of processing paths, each of said processing paths for processing instructions on M-bit data words; and

a plurality of register files, each having Q-number of registers, said Q-number of registers being M-bits wide;

wherein said Q-number of registers within each of said plurality of register files are either private or global registers, and wherein when a value is written to one of said Q-number of said registers which is a global register within one of said plurality of register files, said value is propagated to a corresponding global register in the other of said plurality of register files, and wherein when a value is written to one of said Q-number of said registers which is a private register within one of said plurality of register files, said value is not propagated to a corresponding register in the other of said plurality of register files.

- 2. (Original) The processing core as recited in claim 1, wherein every two of said N-number of processing paths share one of said plurality of register files.
- 3. (Original) The processing core as recited in claim 1, wherein a processing instruction comprises N-number of P-bit instructions appended together to form a very long instruction word (VLIW), and said N-number of processing paths process N-number of P-bit instructions in parallel.
- 4. (Original) The processor chip as recited in claim 3, wherein M=64, Q=64, and P=32.

Appl. No. 09/802,289 Amdt. dated July 21, 2004 Reply to Office Action of April 27, 2004 PATENT

- 5. (Original) The processing core as recited in claim 1, wherein said processing pipeline comprises an execute stage which includes an execute unit for each of said N-number of M-bit processing paths, each of said execute units comprising an integer processing unit, a load/store processing unit, a floating point processing unit, or any combination of one or more of said integer processing units, said load/store processing units, and said floating point processing units.
  - 6. (Original) The processing core as recited in claim 5, wherein an integer processing unit and a floating point processing unit share one of said plurality of register files.
  - 7. (Original) The processing core as recited in claim 1, wherein Q=64, and a 64-bit special register stores bits indicating whether a register in a register file is a private register or a global register, each bit in the 64-bit special register corresponding to one of said registers in said register file.
  - 8. (Original) The processing core as recited in claim 1, wherein each of said plurality of register files is connected to a bus, and a value written to a global register in one of said plurality of register files is propagated to a corresponding global register in the other of said plurality of register files across said bus.
  - 9. (Original) The processing core as recited in claim 1, wherein said plurality of register files are connected together in serial, and a value written to a first global register in a first of said plurality of register files is propagated to a corresponding first global register in a second of said plurality of register files connected directly to said first of said plurality of register files.
  - 10. (Currently Amended) A VLIW processing core comprising:
    one or more processing pipelines each including a fetch stage, a decode stage, an
    execute stage, and a write-back stage, said execute stage having an execute unit comprising an
    integer processing unit, a load/store processing unit, a floating point processing unit, or any

Appl. No. 09/802,289 Amdt. dated July 21, 2004 Reply to Office Action of April 27, 2004

combination of one or more of said integer processing units, said load/store processing units, and said floating point processing units; and

> a register file for each of said one or more processing pipelines; wherein:

an integer processing unit and a floating point processing unit within said one or more processing pipelines both access said register file, the register file is comprised of Q-number of registers, said Q-number of registers are either private or global

registers,

<u>when a value is written to one of said Q-number of said</u> registers that is a global register within one of said plurality of register files, said value is propagated to a corresponding global register in another register file within the VLIW processing core, and

when a value is written to one of said O-number of said registers that is a private register within one of said plurality of register files, said value is not propagated to a corresponding register in another register file within the VLIW processing core.

(Currently Amended) In a computer system, a scalable computer 11. processing architecture, comprising:

one or more processor chips, each comprising:

a processing core, including:

a processing pipeline having N-number of processing paths, each of said processing paths for processing instructions on M-bit data words; and

a plurality of register files, each having Q-number of registers, said Qnumber of registers being M-bits wide;

an I/O link configured to communicate with other of said one or more processor chips or with I/O devices;

Appl. No. 09/802,289 Amdt. dated July 21, 2004 Reply to Office Action of April 27, 2004

> a communication controller in electrical communication with said processing core and said I/O link;

said communication controller for controlling the exchange of data between a first one of said one or more processor chips and said other of said one or more processor chips;

wherein:

said computer processing architecture can be scaled larger by connecting together two or more of said processor chips in parallel via said I/O links of said processor chips, so as to create multiple processing core pipelines which share data therebetween,

said Q-number of registers within each of said plurality of register files are either private or global registers,

when a value is written to one of said Q-number of said registers which is a global register within one of said plurality of register files, said value is propagated to a corresponding global register in the other of said plurality of register files, and

when a value is written to one of said O-number of said registers which is a private register within one of said plurality of register files, said value is not propagated to a corresponding register in the other of said plurality of register file.

- The computer processing architecture as recited in claim 12. (Original) 11, wherein in said processing core of each of said processor chips, every two of said N-number of processing paths share one of said plurality of register files.
- The computer processing architecture as recited in claim (Original) 13. 11, wherein a processing instruction comprises N-number of P-bit instructions appended together to form a very long instruction word (VLIW), and said N-number of processing paths process Nnumber of P-bit instructions in parallel.

Appl. No. 09/802,289 Amdt. dated July 21, 2004 Reply to Office Action of April 27, 2004

- 14. (Original) The computer processing architecture as recited in claim 13, wherein M=64, Q=64, and P=32.
- 15. (Original) The computer processing architecture as recited in claim 11, wherein said processing pipeline comprises an execute stage which includes an execute unit for each of said N-number of M-bit processing paths, each of said execute units comprising an integer processing unit, a load/store processing unit, a floating point processing unit, or any combination of one or more of said integer processing units, said load/store processing units, and said floating point processing units.
- 16. (Original) The computer processing architecture as recited in claim 15, wherein an integer processing unit and a floating point processing unit share one of said plurality of register files.
- 17. (Canceled) Please cancel claim 17 without disclaimer of or prejudice to the subject matter contained therein.
- 18. (Currently Amended) The computer processing architecture as recited in claim 11 17, wherein Q=64, and a 64-bit special register stores bits indicating whether a register in a register file is a private register or a global register, each bit in the 64-bit special register corresponding to one of said registers in said register file.
- 19. (Currently Amended) The computer processing architecture as recited in claim 11 17, wherein each of said plurality of register files is connected to a bus, and a value written to a global register in one of said plurality of register files is propagated to a corresponding global register in the other of said plurality of register files across said bus.
- 20. (Original) The computer processing architecture as recited in claim 19, wherein said plurality of register files are connected together in serial, and a value written to a first global register in a first of said plurality of register files is propagated to a corresponding

Appl. No. 09/802,289 Amdt. dated July 21, 2004 Reply to Office Action of April 27, 2004 **PATENT** 

first global register in a second of said plurality of register files connected directly to said first of said plurality of register files.